

PENTAX

Positioning Systems

Precision Satellite Surveying

G6 Series

G6TiE | G6NiE

GPS | GLONASS | BEIDOU | SBAS | GALILEO



PENTAX

- + Compact and durable metal housing
- + Better dust and weather resistance (IP67)
- + Equipped with TILT sensor that works as an electric bubble

TI Asahi Co.,Ltd
Aiming at the future together!

GNSS SPECIFICATIONS

Model		G6TiE	G6NiE
Channel Configuration		220 channels (dual frequency) for GPS, GLONASS, Galileo, Beidou and SBAS	555 channels (dual frequency) for GPS, GLONASS, Beidou and SBAS
Receiver Board		Trimble BD930	NovAtel 719
Single Tracked	GPS	L1 C/A, L2E, L2C, L5	L1 C/A, L1C, L2C, L2P, L5
	GLONASS	L1 C/A, L2C/A, L3CDMA	L1 C/A, L2C, L2P, L3, L5
	BEIDOU	B1 / B2	B1, B2, B3
	Galileo	E1, E5A, E5B, E5AltBOC	E1, E5 AltBOC, E5a, E5b, E6
	QZSS	L1 C/A, L1 SAIF, L2C, L5	L1 C/A, L1C, L2C, L5, L6
	SBAS	L1 C/A, L5	L1, L5
Position Accuracy		Horizontal / Vertical	
	SBAS	0.5 m / 0.85 m	
	DGPS	0.25 m + 1 ppm / 0.5 m + 1 ppm	
RTK Performance	Horizontal Accuracy	0.008 m + 1 ppm	0.010 m + 1 ppm
	Vertical Accuracy	0.015 m + 1 ppm	0.020 m + 1 ppm
	Average Time to Work	Typ. < 10 sec.	
	Availability/Initialization Reliability	> 99.9%	
Static Performance	Horizontal Accuracy	2.5 mm + 0.5 ppm	
	Vertical Accuracy	5 mm + 0.5 ppm	
Ports		Lemo 5-pin, external radio and power supply	
		Lemo 7-pin, serial port and USB	
Power	Internal Battery	3,350 mAh / 7.4V x2	
	Current Drain	0.35A / 12V	
		1.25A / 12V max.	
	Battery Running Time	Approx. 12 hr: Rover, 10 hr: Base	
Weight		1.1 kg with 2 batteries	
Dimensions		Ø 130 mm x H 100 mm	
Environmental Specifications	Operating Temperature	-30 °C to +65 °C	
	Storage Temperature	-30 °C to +65 °C	
	Shock/Drop	2 m	
Velocity Accuracy	Standalone	0.007 m/sec, 0.020 m/sec	0.03 m/s RMS
Data Output	Raw Data	up to 20 Hz	up to 5 Hz (50 Hz optional)
	NMEA Data	1 Hz, 2 Hz, 5 Hz, 10 Hz, 20 Hz	Default 5 Hz
		RTCM Ver 2.1, 2.2, 2.3, 3.0, 3.1, 3.2	
		CMR, CMR+, sCMRx	
Time to First Fix	Cold Start	< 45 sec	< 50 sec
	Warm Start	After power-on < 30 sec	After power-on < 35 sec
		Re-acquisition < 2 sec	Re-acquisition < 1 sec
Tilt Sensor		IMU / Electric Bubble	
		Range 30°/ < 30mm	
Memory		Internal 4 GB and MicroSD 4 GB	
RoHS		—	
Waterproofing		IP67	
Certification		CE	
Standard Accessories		2 x Li-Ion rechargeable battery pack	
		Battery charger + AC Adapter	
		UHF radio antenna (longer one)	
		5/8 inch screw adapter	
		Lemo 7-pin communication cable	

PENTAX Positioning System is dedicated to providing customers with first class positioning system products and freedom of choice. We have carefully designed high-quality products to meet the needs of today's surveyors based on the experience of many years involved in instrument design and construction. Our engineers have been involved in Survey products since the beginning of the Satellite Surveying Era. We are committed to ease of use, a low cost of ownership and flexibility to accommodate different working environments. Our close partners are carefully chosen and are committed to these values as we are.

TI Asahi Co., Ltd.
International Sales Department
 4-3-4 Ueno Iwatsuki-Ku, Saitama-Shi
 Saitama, 339-0073 Japan
 Tel.: +81-48-793-0118
 Fax: +81-48-793-0128
 E-mail: International@tiasahi.com

www.pentaxsurveying.com/en/

Your Official Pentax Dealer



The CE marking assures that this product complies with the requirements of the EC directive for safety.



Member symbol of the Japan Surveying Instruments Manufacturers' Association representing the high quality surveying products.